

AUTOMATIC QUAD DRIVE CARTON SEALER

The BestPack[™] AQ Series is an fully automatic, carton sealer designed to meet the needs of uniform in-line carton closure applications. The four belt drives are powered by three electric 110V UL approved motors. The guad-belt technology allows for more carton stability and effective sealing in rugged applications. The AQ model, that closes all top flaps and seals the top & bottom of the carton, is designed with a stable four-column support structure.

NOW EQUIPPED WITH OUR DATA ADVANTAGE SYSTEM!*



45-60 PSI, 4-5 SCFM

Air

Requirements



UNIFORM CARTONS



TOP & BOTTOM SEAL

632-657 LBS


Shipping

Weight

110 VOLTS 60 HZ

Power Requirements

CARTON RANGE



Length (min. - max.) (8.0" - 27.5")

Width (min. - max.)

(7.5" - 20.0")

Height (min. - max.) (5.5" - 20.0")

Specifications based on AQ22-2

WWW.BESTPACK.COM

Speed

UP TO 57 CPM

STANDARD FEATURES

- In-Line Automatic Top Flap Folding
- Adjustable Bed Height from: 22.5" to 30.0"
- Width/Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Upper Side Compression Unit
- Interlock Safety Gates in the Kicker Station
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Capable of Interchanging 2" or 3" Tape Heads

• Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise **Reduction Arm**

DATA ADVANTAGE SYSTEM COMES WITH:

- Low Tape/No Tape Monitoring
- Improved Electrical Efficiency
- Jam Detection
- Machine Performance Tracking
- and more features to improve your experience...

- **OPTIONS**
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
 Additional Safety Guarding Available
- VFD Motor Upgrade (Up to 150+ ft. per min.)
- Locking Heavy-Duty Casters
- Compatible Indexer: ARX Model

VERSION 4.7_0822

EXPERIENC COMMUN E \mathbf{C} © 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT "Spare Parts Kits may vary based on machine" Minimize downtime with BestPack's Spare Parts Kit.



ADDITIONAL SAFETY GUARDING Add additional protective measures

that prevent workplace injuries with additional safety gates around your equipment.



INDEXER STATION The indexer's function is to separate and time cartons going into the carton sealer.



FOOD GRADE 304 STAINLESS STEEL This machine is available in 304 stainless steel which is food grade safe for food applications.



HIGH SPEED MOTOR High Speed Motor Upgrade (up to 125 ft.)

POPULAR AQ MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH X WIDTH X HEIGHT	CARTON RANGE**** LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.****	SHIPPING WEIGHT (LBS)
AQ12-2 2" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (7.5" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	632
AQ12-2H** 2" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (7.5" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 57	632
AQ12-3 3" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (7.5" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	632
AQ12-3H** 3" Tape Head	(70.2") × (26.5") × (68.0")*	(8.0" - 25.5") × (7.5" - 14.0") × (6.5" - 20.0")	(22.5" - 30.0")	Up to 57	632
AQ22-2 2" Tape Head	(77.5") × (33.8") × (73.0")*	(8.0" - 27.5") × (7.5" - 20.0") × (5.5" - 20.0")	(23.5" - 30.0")	Up to 34	645
AQ22-2H** 2" Tape Head	(77.5") x (33.8") x (73.0")*	(8.0" - 27.5") x (7.5" - 20.0") x (5.5" - 20.0")	(23.5" - 30.0")	Up to 57	645
AQ22-3 3" Tape Head	(77.5") x (33.8") x (73.0")*	(8.0" - 27.5") x (7.5" - 20.0") x (5.5" - 20.0")	(23.5" - 30.0")	Up to 34	645
AQ22-3H** 3" Tape Head	(77.5") × (33.8") × (73.0")*	(8.0" - 27.5") × (7.5" - 20.0") × (5.5"- 20.0")	(23.5" - 30.0")	Up to 57	645
AQ33-3 3" Tape Head	(83.0") × (43.0") × (81.0")*	(8.0" - 27.5") x (7.5" - 27.5") x (6.0" - 30.0")	(23.5" - 30.0")	Up to 34	657
Information subject to change without notice. * Safety Gates are an Additional 20" L ** High Sp ** High Sp					

*** Outside Dimensions Only

**** Based on Customer Application



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.