

# SCRAP CHOPPERS

## MATERIAL REFERENCE

- ¾" x .031" steel banding with clip
- ⅝" x .030" plastic/poly straps
- ¾" x .050" poly straps

## DIMENSIONAL DATA

- Infeed Opening.....1" x 1 ⅝"
- Overall.....19" x 30" x 19"
- Weight.....136 lbs.
- Shipping Weight.....220 lbs.

## PERFORMANCE DATA

- Electric Motor Power.....½ HP
- Infeed Speed.....123 fpm
- Cut Length.....2 ⅝"
- Number of Stationary Knives.....1
- Number of Rotating Knives.....1

## STANDARD ELECTRICAL OPTIONS

- 1-Phase - 120 volt - 60 Hz - 8 amps

*The Model 300 (1-phase 120 volt) is standard with an 6 foot 15 amp power supply cord and molded plug. Voltages other than the standard above, are subject to a rewind charge.*

## HOW IT WORKS

Just introduce the material (banding) into the infeed funnel. The feedworks (pinch rolls) will then grab the material and pull it into the rotating knife path. The feedworks will continue to pull at a rate of 123 feet per minute until the material is consumed or the operator releases the feedworks via the release lever.

## CONSTRUCTION FEATURES

- Easy to reach "Feedworks Release" hand lever
- Infeed funnel with "Anti-Kickback" flap
- Knives can be rotated (4 times) for extended life
- Will fit barrels with a diameter as small as 22 ¼"
- Assembled in Gold Hill, Oregon
- Full one year warranty



# MODEL 300

Quickly becoming a common fixture on loading docks across the country.

The Model 300 is ideal for plastic banding and steel banding. This model is an economical answer to keeping your warehouse clean and free of scrap; eliminating employee injuries and reducing disposal costs. The Model 300 Bandit is a perfect solution for the packaging, food and beverage industries! This scrap chopper is designed to fit on a barrel or can sit on an optional stand.

**Your company needs this chopper because:** It is the ideal unit for your loading dock, lumber yard or warehouse situation. Piling banding only makes a mess...chop it before you drop it!

