



620

VIBAC® BOPP BOX SEALING TAPE 620

These cold temperature packaging tapes have been formulated to be used in applications at refrigerated temperatures or at room temperature and then stored in low temperature environments which include produce packaging, dairy facilities, meat and poultry processing plants. Perform very well in cold weather moving/ storage conditions and unheated warehouses located in cold weather climates.

PROPERTIES			
Total thickness micron	49 micron	Total thickness mils	1.930 mils
Business	Industrial Professional	Industry	Carton Sealing Cold Storage
Backing Type	BOPP	Backing thickness micron	29 micron
Adhesive type	Synthetic Rubber	Color	Clear
Tensile strength kg/cm	4,64 kg/cm	Elongation at break	165 %
Adhesion to steel g/cm	295,7 g/cm	Rolling ball test (RBT) cm	<2 cm
Shear on cardboard	>16.67 hours	Backing thickness mils	1.160 mils
Tensile strength lb./inch	26.000 lb./inch	Adhesion to steel oz./inch	27 oz./inch
Rolling ball test (RBT) inch	<0.78 inch	Service Temperature F° (Min / Max)	(-15)/100 °F
Service Temperature C° (Min / Max)	(-26)/38 °C	Application Temperature F° (Min / Max)	20/110 °F
Application Temperature C° (Min / Max)	(-7)/46 °C	Available width	72.000 mm 48.000 mm
Available length	100.000 m	Packaging type	6 rolls flat pack

620