



730

VIBAC® BOPP BOX SEALING TAPE 730

This High Performance packaging tape was designed for carton sealing, splicing, bundling and other extra heavy packaging applications. This product offers superior adhesive power for bulky and heavy boxes.

PROPERTIES			
Total thickness micron	62 micron	Total thickness mils	2.440 mils
Business	Industrial Professional	Industry	Bundling Carton Sealing Splicing
Backing Type	BOPP	Backing thickness micron	40 micron
Adhesive type	Synthetic Rubber	Color	Clear
Tensile strength kg/cm	6,42 kg/cm	Elongation at break	200 %
Adhesion to steel g/cm	611,8 g/cm	Rolling ball test (RBT) cm	<2 cm
Shear on cardboard	>133.34 hours	Backing thickness mils	1.570 mils
Tensile strength lb./inch	36.000 lb./inch	Adhesion to steel oz/inch	56 oz./inch
Rolling ball test (RBT) inch	<0.78 inch	Service Temperature F° (Min / Max)	30/140 °F
Service Temperature C° (Min / Max)	(-2)/60 °C	Application Temperature F° (Min / Max)	50/110 °F
Application Temperature C° (Min / Max)	(10)/43 °C	Available width	72.000 mm 48.000 mm 36.000 mm 144.000 mm 96.000 mm
Available length	50.000 m 100.000 m 55.000 m	Packaging type	6 rolls flat pack